



DEVIreg™ 130

The DEVIreg™130 is an electronic thermostat installed directly onto a wall surface. It is supplied with an NTC Sensor probe to control to the desired floor temperature.

The thermostat has a dial for setting the desired temperature from OFF and a scale from 1 to 10 (each step equates to approximately 9 C°).

An LED indicates the heating status - Red (Heating) and Green (on Standby at set-point temperature).


Benefits:


- 2-pole safety breaker
- Low standby consumption
- Sensor failure monitoring
- LED indication for fault

Standard compliance:

- EN/IEC 60730-1 (general) and EN/IEC 60730-2-9 (thermostat)

Approvals:



Type	Value
Operation voltage	220 V- 240V~ 50/60 Hz
Power Consumption	Max. 5 W
Relay:	
Resistive load	Max. 16 amps / 2300 W @ 230V
Inductive load	Cos Φ = 0.3 max. 1A
Sensing unit	NTC 15 kOhm at 25° C
Hysteresis	±0.2° C
Ambient temperature	0° C to +30° C
Frost protection	5° C - ❄️
Temperature range	OFF, 5° C to +45° C
Cable specification max	1 x 4 mm ² or 2 x 2,5 mm ²
Ball pressure test temperature	75° C
Pollution degree	2 (domestic use)
Controller type	1 C
Storage temperature	-20° C to +65° C
IP class	30
Protection class	Class II - 
Dimensions (H/W/D)	82 mm x 82 mm x 36 mm
Weight	90 g

Types

Code No.	Name	Description
01-140F1010	DEVIreg™ 130	Surface mounted Manual thermostat with Floor temperature Sensor probe.

