



DEVIreg™ 132

The DEVIreg™132 is an electronic thermostat installed directly onto a wall surface. It is supplied with a built-in sensor to control the Room Air temperature and an additional sensor probe to limit the maximum floor temperature. Ideal for wooden or vinyl floors.

The thermostat has a dial for setting the desired Room temperature from OFF and a scale from 5° C to 45° C. Floor temperature limit adjustable & set during installation.

An LED indicates the heating status - Red (Heating) and Green (on Standby at set-point temperature).

Benefits:


- 2-pole safety breaker
- Low standby consumption
- Sensor failure monitoring
- LED indication for fault

Standard compliance:

- EN/IEC 60730-1 (general) and EN/IEC 60730-2-9 (thermostat)

Approvals:



| Type | Value |
|--------------------------------|--|
| Operation voltage | 220 V- 240V~ 50/60 Hz |
| Power Consumption | Max. 5 W |
| Relay: | |
| Resistive load | Max. 10 amps / 2300 W @ 230V |
| Inductive load | Cos Φ = 0.3 max. 1A |
| Sensing unit | NTC 15 kOhm at 25° C |
| Hysteresis | ±0.2° C |
| Ambient temperature | 0° C to +30° C |
| Frost protection | 5° C - ❄️ |
| Temperature range | OFF, 5° C to +45° C |
| Cable specification max | 1 x 4 mm ² or 2 x 2,5 mm ² |
| Ball pressure test temperature | 75° C |
| Pollution degree | 2 (domestic use) |
| Controller type | 1 C |
| Storage temperature | -20° C to +65° C |
| IP class | 30 |
| Protection class | Class II -  |
| Dimensions (H/W/D) | 82 mm x 82 mm x 36 mm |
| Weight | 90 g |

Types

| Code No. | Name | Description |
|-------------|-------------|---|
| 01-140F1011 | DEVIreg™132 | Surface mounted Manual thermostat with built-in Room Air temperature sensor and Floor temperature Limit Sensor probe. |

